



Ferris[®] Casting Wax Sheets

Description

Ferris Casting Wax Sheets feature a highly accurate uniform thickness of +/- 0.001 and are used for a wide variety of applications. Pliable at room temperature, they can be transformed to any shape and are easily cut with a knife or scissors. For additional flexibility, Casting Wax can be placed in warm water, to soften.

Physical Properties

Color	Clear, Green, or Pink
Ring & Ball Softening Point (°F)	169 (+/-6)
Density	0.92 (+/-0.05)
Flash Point (°F)	465

Ordering Information

Size	Thickness		Sheets/Pkg.
08 Gauge	.129"	3.3 mm	8
10 Gauge	.102"	2.6 mm	8
12 Gauge	.081"	2.1 mm	8
14 Gauge	.064"	1.6 mm	16
16 Gauge	.051"	1.3 mm	16
18 Gauge	.040"	1.0 mm	16
20 Gauge	.032"	0.8 mm	32
22 Gauge	.025"	0.6 mm	32
24 Gauge	.020"	0.5 mm	32
26 Gauge	.015"	0.4 mm	32
28 Gauge	.012"	0.3 mm	32
30 Gauge	.010"	0.25 mm	32

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no event shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT