SAFETY DATA SHEET

MINERALISED METHYLATED SPIRITS

Page 1 Issued: 12/01/2006 Revision No: 1

Sent to: NEIL

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: MINERALISED METHYLATED SPIRITS

Synonyms: COMPLETELY DENATURED ALCOHOL (CDA)

Use of substance / preparation: Used as a thinner/solvent.

Company name: John Myland Ltd

80 Norwood High Street West Norwood

London

SE27 9NW

Tel: 0208 670 9161

2. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Harmful by inhalation, in contact with skin and if swallowed. Harmful: possible

risk of irreversible effects through inhalation, in contact with skin and if swallowed.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: ETHANOL >90%

EINECS: 200-578-6 CAS: 64-17-5

[F] R11

• METHANOL 1-10%

EINECS: 200-659-6 CAS: 67-56-1

[F] R11; [T] R23/24/25; [T] R39/23/24/25

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

SAFETY DATA SHEET MINERALISED METHYLATED SPIRITS

5. FIRE-FIGHTING MEASURES		
Extinguishing media:	Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool	
	containers.	
Exposure hazards:	Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour	
	may travel considerable distance to source of ignition and flash back.	
Protection of fire-fighters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin	
	and eyes.	
6. ACCIDENTAL RELEASE MEASURES		
Personal precautions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from	
	downwind. If outside keep bystanders upwind and away from danger point. Mark out the	
	contaminated area with signs and prevent access to unauthorised personnel. Turn leaking	
	containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.	
Environmental precautions:	Do not discharge into drains or rivers. Contain the spillage using bunding.	
Clean-up procedures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by	
	an appropriate method. Do not use equipment in clean-up procedure which may produce	
	sparks.	
7. HANDLING AND STORAGE		
Handling requirements:	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do	
	not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is	
	forbidden. Use non-sparking tools.	
Storage conditions:	Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of	
	ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and	
	electrical equipment are not a source of ignition.	
8. EXPOSURE CONTROLS / PERSONAL PROTECTION		
Hazardous ingredients:	ETHANOL	
	WEL (8 hr TWA): 1920 mg/m3	
•	METHANOL	
	WEL (8 hr TWA): 266 mg/m3 WEL (15 min STEL): 333 mg/m3	
Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not	
	a source of ignition.	
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.	
Hand protection:	Impermeable gloves.	
Eye protection:	Safety glasses. Ensure eye bath is to hand.	
Skin protection:	Impermeable protective clothing.	

Page 2

SAFETY DATA SHEET

MINERALISED METHYLATED SPIRITS

9. PHYSICAL AND CHEMICAL PROPERTIES		
State:	Liquid	
Colour:	Purple	
Odour:	Unpleasant	
Flammability limits %: lower:	3.5	
upper:	19	
Flash point°C:	13	
Relative density:	0.825 20	
10. STABILITY AND REACTIVITY		
Stability:	Stable under normal conditions. Stable at room temperature.	
Conditions to avoid:	Heat. Hot surfaces. Sources of ignition. Flames.	
Materials to avoid:	Strong oxidising agents. Strong acids.	
Haz. decomp. products:	In combustion emits toxic fumes.	
11. TOXICOLOGICAL INFORMATION		
Hazardous ingredients:	ETHANOL	
	IVN RAT LD50 1440 mg/kg	
	ORL MUS LD50 3450 mg/kg	
	ORL RAT LD50 7060 mg/kg	
•	METHANOL	
	IVN RAT LD50 2131 mg/kg	
	ORL MUS LD50 7300 mg/kg	
	ORL RAT LD50 5628 mg/kg	
Routes of exposure:	Refer to section 4 of SDS for routes of exposure and corresponding symptoms.	
12. ECOLOGICAL INFORMATION		
Mobility:	Readily absorbed into soil.	
Persistence and degradability:	Biodegradable.	
Bioaccumulative potential:	No bioaccumulation potential.	
Other adverse effects:	Negligible ecotoxicity.	
13. DISPOSAL CONSIDERATIONS		
NB:	The user's attention is drawn to the possible existence of regional or national regulations	
	regarding disposal.	
14. TRANSPORT INFORMATION		

ADR / RID

SAFETY DATA SHEET

MINERALISED METHYLATED SPIRITS

Packing group: II Classification code: F1 Shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION) Labelling: 3 Hazard ID no: 33 IMDG/IMO **UN no:** 1170 Class: 3 Packing group: II EmS: F-E,S-D Marine pollutant: NO Labelling: 3 IATA / ICAO UN no: 1170 Class: 3 Packing group: II Packing instructions: 305(P&CA); 307(CAO) Labelling: 3 **15. REGULATORY INFORMATION** Hazard symbols: Highly flammable. Harmful. Risk phrases: R11: Highly flammable. R20/21/22: Harmful by inhalation, in contact with skin and if swallowed. R68/20/21/22: Harmful: possible risk of irreversible effects through inhalation, in contact with skin and if swallowed. Safety phrases: S36/37: Wear suitable protective clothing and gloves. Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions. **16. OTHER INFORMATION** Risk phrases used in s.3: R11: Highly flammable. R23/24/25: Toxic by inhalation, in contact with skin and if swallowed. R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact

with skin and if swallowed.

Page 4

SAFETY DATA SHEET MINERALISED METHYLATED SPIRITS

Page 5

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.