

# MacDermid Enthone

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

## SAFETY DATA SHEET

METEX LC 3000

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name** : METEX LC 3000  
**Product code** : 186160

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Industrial cleaners.  
Industrial applications.

#### 1.3 Details of the supplier of the safety data sheet

**e-mail address of person responsible for this SDS** : [sdsuk@macdermid.com](mailto:sdsuk@macdermid.com); [regulatory.de@macdermid.com](mailto:regulatory.de@macdermid.com)

**Supplier** : MacDermid Performance Solutions UK Limited  
198 Golden Hillock Road  
Birmingham  
B11 2PN  
UK

**Information contact** : Tel (+44) 121 606 8100  
[ukcustomer.services@macdermid.com](mailto:ukcustomer.services@macdermid.com)

#### 1.4 Emergency telephone number

##### National advisory body/Poison Centre

**Telephone number** : UK NPIS 0344 892 0111 (Healthcare professionals only)

##### Supplier

**Telephone number** : Carechem24: (+44) 1865 407333; (+44) 1235 239 670 (across Europe)  
**Hours of operation** : 24/7

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

##### Classification according to UK CLP/GHS

Skin Corr. 1B, H314  
Eye Dam. 1, H318  
Carc. 2, H351  
STOT SE 3, H335  
Aquatic Chronic 3, H412

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

## SECTION 2: Hazards identification

### 2.2 Label elements

**Hazard pictograms**



**Signal word**

:  Danger

**Hazard statements**

:  H314 - Causes severe skin burns and eye damage.  
 H335 - May cause respiratory irritation.  
 H351 - Suspected of causing cancer.  
 H412 - Harmful to aquatic life with long lasting effects.

**Precautionary statements**

**Prevention**

:  P280 - Wear protective gloves, protective clothing and eye or face protection.

**Response**

:  P304 + P310 - IF INHALED: Immediately call a POISON CENTER or doctor.  
 P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
 P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

**Storage**

:  P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

**Disposal**

:  P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Hazardous ingredients**

:  Alcohols, C9-11-iso-, C10-rich, ethoxylated  
 Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated,  
 Me sulfates (salts)  
 2-aminoethanol  
 trisodium nitrilotriacetate

**Supplemental label elements**

:  Not applicable.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**

:  Not applicable.

**Special packaging requirements**

### 2.3 Other hazards

**Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**

:  This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**Other hazards which do not result in classification**

:  None known.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

: Mixture

Product/ingredient name	Identifiers	%	Classification	Type
<input checked="" type="checkbox"/> Alcohols, C9-11-iso-, C10-rich, ethoxylated	EC: Polymer	≤10	Acute Tox. 4, H302	[1]
<input checked="" type="checkbox"/> Quaternary ammonium compounds, coco alkylbis(hydroxyethyl)methyl, ethoxylated, Me sulfates (salts)	CAS: 78330-20-8	≤10	Eye Dam. 1, H318	[1]
<input checked="" type="checkbox"/> 2-aminoethanol	CAS: 68989-03-7	≤10	Eye Dam. 1, H318 Aquatic Chronic 2, H411	[1] [2]
	REACH #: 01-2119486455-28	≤10	Acute Tox. 4, H302	[1] [2]
	EC: 205-483-3		Acute Tox. 4, H312	
	CAS: 141-43-5		Acute Tox. 4, H332 Skin Corr. 1B, H314	

### SECTION 3: Composition/information on ingredients

1-aminopropan-2-ol	Index: 603-030-00-8 REACH #: 01-2119475331-43 EC: 201-162-7 CAS: 78-96-6 Index: 603-082-00-1	≤3	Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 3, H412 Acute Tox. 4, H312 Skin Corr. 1B, H314 Eye Dam. 1, H318	[1]
Alcohols, C11-15-secondary, ethoxylated	EC: Polymer CAS: 68131-40-8	≤3	Skin Irrit. 2, H315 Eye Dam. 1, H318	[1]
Glycine, N,N-bis(carboxymethyl)-, sodium salt, hydrate (1:3:1)	REACH #: 01-2119519239-36 EC: 225-768-6 CAS: 18662-53-8 Index: 607-620-00-6	≤3	Acute Tox. 4, H302 Eye Irrit. 2, H319 Carc. 2, H351	[1]
			<b>See Section 16 for the full text of the H statements declared above.</b>	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## SECTION 4: First aid measures

**Protection of first-aiders** :  No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Over-exposure signs/symptoms

- Eye contact** :  Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** :  Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** :  Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** :  Adverse symptoms may include the following:  
stomach pains  
Corrosive to the digestive tract.  
Causes burns.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** :  In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** :  No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media** :  Non-combustible.  
Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** :  None known.

### 5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** :  In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous combustion products** :  Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
sulfur oxides  
metal oxide/oxides

### 5.3 Advice for firefighters

- Special protective actions for fire-fighters** :  Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** :  Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : Specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

- 6.2 Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

## SECTION 7: Handling and storage

The temperature range listed here will maintain the quality of the material during its specified shelf-life. This temperature range restriction is not required to maintain safe storage conditions.

Store between the following temperatures: 5 to 40°C (41 to 104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### 7.3 Specific end use(s)

**Recommendations** : No specific measures identified.

**Industrial sector specific solutions** : No specific measures identified.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
2-aminoethanol	<b>EH40/2005 WELs (United Kingdom (UK), 1/2020). Absorbed through skin.</b> STEL: 7.6 mg/m <sup>3</sup> 15 minutes. STEL: 3 ppm 15 minutes. TWA: 1 ppm 8 hours. TWA: 2.5 mg/m <sup>3</sup> 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### EU DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
2-aminoethanol	DNEL	Long term Inhalation	0.18 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term Inhalation	0.28 mg/m <sup>3</sup>	General population	Local
	DNEL	Long term Inhalation	0.51 mg/m <sup>3</sup>	Workers	Local
	DNEL	Long term Inhalation	1 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	1.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.5 mg/kg bw/day	General population	Systemic
1-aminopropan-2-ol	DNEL	Long term Oral	3 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	0.76 mg/kg bw/day	General population	Systemic
Glycine, N,N-bis(carboxymethyl)-, sodium salt, hydrate (1:3:1)	DNEL	Long term Inhalation	3.6 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Oral	0.3 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	0.5 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	0.8 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Short term Inhalation	1.75 mg/m <sup>3</sup>	General population	Systemic
	DNEL	Long term	3.2 mg/m <sup>3</sup>	Workers	Systemic

**SECTION 8: Exposure controls/personal protection**

	DNEL	Inhalation Short term Inhalation	5.25 mg/m <sup>3</sup>	Workers	Systemic
--	------	--	------------------------	---------	----------

**EU PNECs**

No PNECs available

**8.2 Exposure controls**

**Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

**Individual protection measures**

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If inhalation hazards exist, a full-face respirator may be required instead. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Face shield. Use eye protection according to EN 166.

**Skin protection**

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.  
Recommendations: In splash contact: 1 - 4 hours (breakthrough time): neoprene. Long term exposure: > 8 hours (breakthrough time): butyl rubber, fluorinated rubber. (thickness: 0.5 mm) Wear suitable gloves tested to EN374.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**9.1 Information on basic physical and chemical properties****Appearance**

**Physical state** : Liquid.

**Colour** : Yellow. Brown. [Transparent]

**SECTION 9: Physical and chemical properties**

- Odour** : Characteristic.
- Odour threshold** : There are no data available on the mixture itself.
- Melting point/freezing point** : There are no data available on the mixture itself.
- Initial boiling point and boiling range** :  10°C (230°F)
- Flammability (solid, gas)** : There are no data available on the mixture itself.
- Upper/lower flammability or explosive limits** : There are no data available on the mixture itself.
- Flash point** :

Ingredient name	Closed cup			Open cup		
	°C	°F	Method	°C	°F	Method
<input checked="" type="checkbox"/> aminopropan-2-ol	77	170.6				

- Auto-ignition temperature** :

Ingredient name	°C	°F	Method
<input checked="" type="checkbox"/> cohols, C9-11-iso-, C10-rich, ethoxylated	>150	>302	

- Decomposition temperature** : There are no data available on the mixture itself.
- pH** : 9.5 to 11
- Viscosity** : There are no data available on the mixture itself.
- Solubility(ies)** :  
Not available.

- Solubility in water** : There are no data available on the mixture itself.
- Miscible with water** : es.
- Partition coefficient: n-octanol/ water** : Not applicable.

- Vapour pressure** :

Ingredient name	Vapour Pressure at 20°C			Vapour pressure at 50°C		
	mm Hg	kPa	Method	mm Hg	kPa	Method
<input checked="" type="checkbox"/> water	23.8	3.2				

- Evaporation rate** : There are no data available on the mixture itself.
- Relative density** : There are no data available on the mixture itself.
- Density** : .01 to 1.04 g/cm<sup>3</sup> [20°C (68°F)]
- Vapour density** : There are no data available on the mixture itself.
- Explosive properties** : There are no data available on the mixture itself.
- Oxidising properties** : There are no data available on the mixture itself.
- Particle characteristics**
- Median particle size** : Not applicable.

**9.2 Other information**

- SAPT** : Not relevant/applicable due to nature of the product.

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity** : Extremely reactive or incompatible with the following materials: oxidising materials and acids.  
Highly reactive or incompatible with the following materials: metals.
- 10.2 Chemical stability** : No specific stability hazards associated with this product.  
The product is stable.



**SECTION 10: Stability and reactivity**

**10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

**10.5 Incompatible materials** : No specific data.

**10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Alcohols, C9-11-iso-, C10-rich, ethoxylated	LD50 Dermal	Rat	>2000 mg/kg	-
2-aminoethanol	LD50 Oral	Rat	>300 mg/kg	-
1-aminopropan-2-ol	LD50 Oral	Rat	1720 mg/kg	-
	LD50 Oral	Rat	1715 mg/kg	-

**Conclusion/Summary** : Not tested

**Acute toxicity estimates**

Product/ingredient name	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
METEX LC 3000	4472.5	11519.5	N/A	N/A	21.2
Alcohols, C9-11-iso-, C10-rich, ethoxylated	500	N/A	N/A	N/A	N/A
2-aminoethanol	1720	1100	N/A	N/A	1.5
1-aminopropan-2-ol	N/A	1100	N/A	N/A	N/A
Glycine, N,N-bis(carboxymethyl)-, sodium salt, hydrate (1:3:1)	500	N/A	N/A	N/A	N/A

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-aminoethanol	Eyes - Severe irritant	Rabbit	-	250 ug	-
	Skin - Moderate irritant	Rabbit	-	505 mg	-
1-aminopropan-2-ol	Eyes - Severe irritant	Rabbit	-	24 hours 250 ug	-
	Eyes - Severe irritant	Rabbit	-	970 ug	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
Alcohols, C11-15-secondary, ethoxylated	Skin - Moderate irritant	Rabbit	-	485 mg	-
	Eyes - Mild irritant	Rabbit	-	100 mg	-
	Eyes - Severe irritant	Rabbit	-	1 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-

**Conclusion/Summary**

**Skin** : Not tested

**Eyes** : Not tested

**Respiratory** : Not tested

**Sensitisation****Conclusion/Summary**

**Skin** : Not tested

**Respiratory** : Not tested

**SECTION 11: Toxicological information****Mutagenicity**Conclusion/Summary :  Not tested**Carcinogenicity**Conclusion/Summary :  Not tested**Reproductive toxicity**Conclusion/Summary :  Not tested**Teratogenicity**Conclusion/Summary :  Not tested**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
<input checked="" type="checkbox"/> 2-aminoethanol	Category 3	-	Respiratory tract irritation

**Specific target organ toxicity (repeated exposure)**

Not available.

**Aspiration hazard**

Not available.

Information on likely routes of exposure :  Not tested**Potential acute health effects**Eye contact :  Causes serious eye damage.Inhalation :  May cause respiratory irritation.Skin contact :  Causes severe burns.Ingestion :  Corrosive to the digestive tract. Causes burns.**Symptoms related to the physical, chemical and toxicological characteristics**

**Eye contact** :  Adverse symptoms may include the following:  
 pain  
 watering  
 redness

**Inhalation** :  Adverse symptoms may include the following:  
 respiratory tract irritation  
 coughing

**Skin contact** :  Adverse symptoms may include the following:  
 pain or irritation  
 redness  
 blistering may occur

**Ingestion** :  Adverse symptoms may include the following:  
 stomach pains  
 Corrosive to the digestive tract.  
 Causes burns.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

**Long term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

**SECTION 11: Toxicological information****Potential chronic health effects**

Not available.

- Conclusion/Summary** : Not available.
- General** :  No known significant effects or critical hazards.
- Carcinogenicity** :  Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** :  No known significant effects or critical hazards.
- Reproductive toxicity** :  No known significant effects or critical hazards.

**Other information** :  No known significant effects or critical hazards.

**SECTION 12: Ecological information****12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
<input checked="" type="checkbox"/> -aminoethanol	Acute EC50 8.42 mg/l Fresh water	Algae - Green algae - Desmodesmus subspicatus	72 hours
	Acute LC50 >100000 µg/l Marine water	Crustaceans - Common shrimp, sand shrimp - Crangon crangon - Adult	48 hours
	Acute LC50 170 mg/l Fresh water	Fish - Goldfish - Carassius auratus	96 hours
1-aminopropan-2-ol	Acute LC50 210 mg/l Fresh water	Fish - Goldfish - Carassius auratus	96 hours
Alcohols, C11-15-secondary, ethoxylated	Acute LC50 4600 µg/l Fresh water	Fish - Bluegill - Lepomis macrochirus	96 hours

**Conclusion/Summary** :  Ecological testing has not been conducted on this product.

**12.2 Persistence and degradability**

**Conclusion/Summary** : Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
<input checked="" type="checkbox"/> METEX LC 3000	-	-	Inherent
Alcohols, C9-11-iso-, C10-rich, ethoxylated	-	-	Readily
1-aminopropan-2-ol	-	-	Readily
Alcohols, C11-15-secondary, ethoxylated	-	-	Readily

**12.3 Bioaccumulative potential**

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
<input checked="" type="checkbox"/> -aminoethanol	-1.31	-	low
1-aminopropan-2-ol	-0.96	0.11	low
Alcohols, C11-15-secondary, ethoxylated	5.9	-	high

**12.4 Mobility in soil**

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

**12.5 Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

**SECTION 12: Ecological information****12.6 Other adverse effects** : No known significant effects or critical hazards.**SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

**13.1 Waste treatment methods****Product**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.




**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

**Packaging**

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

**SECTION 14: Transport information**

	<b>ADR/RID</b>	<b>IMDG</b>	<b>IATA</b>
<b>14.1 UN number</b>	UN2735	UN2735	UN2735
<b>14.2 UN proper shipping name</b>	AMINES, LIQUID, CORROSIVE, N.O.S. (2-aminoethanol, 1-aminopropan-2-ol)	AMINES, LIQUID, CORROSIVE, N.O.S. (2-aminoethanol, 1-aminopropan-2-ol)	AMINES, LIQUID, CORROSIVE, N.O.S. (2-aminoethanol, 1-aminopropan-2-ol)
<b>14.3 Transport hazard class(es)</b>	8 	8 	8 
<b>14.4 Packing group</b>	III	III	III
<b>14.5 Environmental hazards</b>	No.	No.	No.

**Additional information**

**ADR/RID** : **Tunnel code** E

**IMDG** : **Emergency schedules** F-A,S-B

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to IMO instruments** : Not applicable - not transported in bulk

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****UK (GB) /REACH****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

**Substances of very high concern**

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

**EU regulations**

**Industrial emissions (integrated pollution prevention and control) - Air** : Not listed

**Industrial emissions (integrated pollution prevention and control) - Water** : Not listed

**15.2 Chemical safety assessment** : This product contains substances for which Chemical Safety Assessments are still required.

**SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** :

- ATE = Acute Toxicity Estimate
- GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EUH statement = GB CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RRN = REACH Registration Number
- SGG = Segregation Group
- vPvB = Very Persistent and Very Bioaccumulative

**Procedure used to derive the classification**

Classification	Justification
<ul style="list-style-type: none"> <li>Skin Corr. 1B, H314</li> <li>Eye Dam. 1, H318</li> <li>Carc. 2, H351</li> <li>STOT SE 3, H335</li> <li>Aquatic Chronic 3, H412</li> </ul>	<ul style="list-style-type: none"> <li>Calculation method</li> <li>Calculation method</li> <li>Calculation method</li> <li>Calculation method</li> <li>Calculation method</li> </ul>

**Full text of abbreviated H statements**

**SECTION 16: Other information**

H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

**Full text of classifications**

Acute Tox. 4	ACUTE TOXICITY - Category 4
Aquatic Chronic 2	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Aquatic Chronic 3	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3
Carc. 2	CARCINOGENICITY - Category 2
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Skin Corr. 1B	SKIN CORROSION/IRRITATION - Category 1B
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2
STOT SE 3	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE - Category 3

**Date of printing** : 19 June 2023

**Date of issue/ Date of revision** : 30 May 2023

**Date of previous issue** : 3 May 2023

**Version** : 1.02

**Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

MacDermid Enthone SDS CLP Europe  
(transfer)